




## Episode Radiance: Audio With Ambiance

The Episode Radiance is an all-in-one solution that unites audio and low voltage landscape lighting into a single, simple system.



### Single-Wire Installation

Simplify wiring with audio and lighting run on a single 2-conductor wire, with patent pending ACE Technology designed by Swarm.

### Mix & Match Solution

Easily combine speakers, lights, mounts and the Radiance subwoofer in an all-in-one system to configure the ideal solution for any need.

### A 360° Solution

You are no longer limited to putting speakers around the perimeter of your yard. The Radiance speakers (and lights) radiate in a 360-degree pattern giving you more flexibility in placement.

### IP-66 Rated

Robust IP-66 rating to ensure no dust, weather or water penetrates the components for reliable installations.

### Durable Build Quality

Constructed of die cast zinc, powder coated, and UV protected for years of reliable use and aesthetics.

### Twist-to-Lock Installation

Radiance system components designed to simply twist to install together, with no additional tools or wiring required.



# Core Components

	ES-RAD-SPK3	ES-RAD-SUB10	ES-RAD-LT3	ES-RAD-MB1-300
	Bollard Speaker	Bollard Subwoofer	Bollard Light	MB-1 Audio / Light Processor
<b>Finished Dimensions:</b>	228 x 84 x 84 (mm) 8.98 x 3.31 x 3.31 (in)	364 x 443 (mm) 14.3 x 17.4 (in)	75 x 84 (mm) 2.95 x 3.31 (in)	103.9 x 222.6 x 230 (mm) 4.09 x 8.76 x 9.06 (in)
<b>Weight:</b>	1.6 kg 3.53 lbs	18.2 kg 40.1 lbs	0.915 kg 2.02 lbs	8.96 kg 19.75 lbs
<b>Frequency Response (+/- 3dB):</b>	140Hz - 20KHz (with DSP)	35Hz - 140Hz	N/A	N/A
<b>Nominal Impedance:</b>	70v only	8 Ohm	N/A	N/A
<b>Tap Settings</b>	2/4/8/16W	N/A	N/A	N/A
<b>Crossover Frequency:</b>	N/A	N/A	N/A	N/A
<b>Power Handling (Max):</b>	16W	500W	N/A	N/A
<b>Efficiency (dB)</b>	85dB	86 dB	N/A	N/A
<b>Adjustments/Switches</b>	Tap switch	N/A	Up / down / both switch	N/A
<b>Brightness (lumens)</b>	N/A	N/A	150 lm up / 175 lm down	N/A
<b>Color Temp (K)</b>	N/A	N/A	2700K	N/A
<b>Woofers Size/Type:</b>	3" (80mm) full range PP dome, neodymium magnet, sealed	10" (270mm) aluminum cone, sealed	N/A	N/A
<b>Connector Type:</b>	Bayonet lock	wire leads, silicone wire nuts	Bayonet lock	6 screw terminal block

# Mounts

	ES-RAD-MNT3-STK	ES-RAD-MNT3-WAL	ES-RAD-MNT3-SRF	ES-RAD-MNT3-PND	ES-RAD-SPKBLNK3
	In-Ground Stake Mount	Wall Mount	Surface Mount	Pendant Mount	Speaker Blank
<b>Finished Dimensions:</b>	317 x 77 (mm) 12.48 x 3.03 (in)	103.3 x 108.4 x 84.4 (mm) 4.07 x 4.27 x 3.32 (in)	84.4 x 84.4 x 35.7 (mm) 3.32 x 3.32 x 1.41 (in)	84.4 x 35.7 (mm) 3.32 x 1.41 (in)	228 x 84 x 84 (mm) 8.98 x 3.31 x 3.31 (in)
<b>Weight:</b>	0.764 kg 1.68 lbs	0.4 kg 0.882 lbs	0.292 kg 0.644 lbs	0.135 kg 0.298 lbs	1.1 kg 2.43 lbs
<b>Connector Type:</b>	wire leads, silicone wire nuts	wire leads, silicone wire nuts	wire leads, silicone wire nuts	wire leads, silicone wire nuts	Bayonet lock